KT SERIES

Unique high-grade appearance, stable quality, cost-effective



*KT series tradition power amplifier have excellent continuous output capacity and provide us traditional excellent sound quality.
* 2 channels 2U high-performance and multi-function design.
* Perfect circuit protection design: power-on buffer, overheating protection, short circuit protection, pressure limit protection, over current protection, over load protection, output DC protection.
* With cost-effective, highly reliable and unique high-grade design appearance is favored by the majority of customers.
* Applications for indoor and outdoor: Entertainment or multimedia.

KT 系列具有独特的高档的设计外观，质量稳定可靠，性价比高

*KT 系列传统功放具有极佳的持续输出能力并为我们提供传统风格的优秀音质。
*2 通道 2U 高性能兼备多功能设计。
*完善的电路保护设计：接上电源的缓冲、过热保护、短路保护、限压保护、过流保护、过载保护、输出直流保护。
*性价比高，质量稳定可靠以及独特的高档的设计外观深受广大用户的喜欢。
*适用范围：娱乐工程和多媒体等。

产品型号 / MODEL NO.	KT500B	KT700B	KT1100B
8Ω 立体声输出功率 / 8Ω Stereo Output Power	500W	700W	1100W
4Ω 立体声输出功率 / 4Ω Stereo Output Power	750W	1000W	1600W
8Ω 桥接 / 8Ω Bridged watts	1500W	2000W	3000W
输出线路 / Output Circuit	AB	H	H
高度 / Height	2U		
频响 / Frequency response	10Hz-20KHz		
总谐波失真/ THD+N	<0.1%		
信噪比 / S/N Ratio	≥100dB		
阻尼系数 / Damping factor	>300		
输入灵敏度 / Input sensitivity	0.775V / 1.0V / 1.4V		
输入阻抗 / Input impedance	>10KOhm (Balance / Unbalance)		
输入接口 / Input connector	Convex / concave terminal XLR		
输出接口 / Output connector	Binding posts, Speakon		
冷却 / Cooling	Variable Speed Fans,Front-To-Rear Airflow		
机身尺寸 / Dimension	480mm * 455mm * 90mm		
净重 / Net weight	19.80 KG	20.30 KG	20.80 KG
毛重 / Gross weight	22.90 KG	23.40 KG	23.90 KG
包装尺寸 / Packing dimension	570mm * 560mm * 160mm		